




## Polystrat XT38-33 is Noise absorbing shim for disc brakes

Hard Steel shim with temperature- and pressure resistant rubber coating. One-sided adhesive coating and perfect damping performance



<b>Basis composition</b>	NBR/Carbon Steel/NBR	<b>Roll</b>	ROLL LENGTH up-to 500 m
<b>Color</b>	Black - Other per request	<b>Width</b>	Up-to 500 mm
<b>Composite and tolerances</b>	Rubber, NBR	0.200 ± 0.015 mm	
	Cold rolled carbon steel	0.380 ± 0.020 mm	
	Rubber, NBR	0.200 ± 0.015 mm	
	PS-adhesive, acrylic	0.080 ± 0.010 mm	
	Release paper, siliconized	0.100 ± 0.020 mm	
	Total without release paper	0.860 ± 0.060 mm	

## Industry / Application

Engines / Compressors / Brake systems / Automotive

## Typical technical data and Properties for KLINGER® Polystrat

Max. creep relaxation	ASTM F38	%	12
Adhesive bonding strength to the steel plate	SAFT	°C	100 - 150
	To steel plate	N/mm	≥ 3
Bonding conditions	Shim connection		
	Temperature of back plate	°C	≥ 20
	Pressure	MPa	2-3
	Pressure time	s	5
Rubber hardness	Shore A ISO 7619-1		70-75
Compression	ISO 815-1	%	25-27
Corrosion	EKB 1102	Grade	0
Storage life (Higher storage temperature and or longer storage time may cause a quality decrease of the product)	DIN 7716	Months	24

All information is based on years of experience in production and operation of sealing elements. However, in view of the wide variety of possible installation and operating conditions one cannot draw final conclusions in all application cases regarding the behaviour in gasket joint. The data may not, therefore, be used to support any warranty claims. This edition cancels all previous issues. Subject to change without notice.

